

Tyrone Camarero Specifications

Tyrone

Camarero DS400TE1U-212RT

Key features

- **Virtualization,Hyperconverge Storage,Cloud Computing,High End Enterprise Server, Flexible Networking Options**
- 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 2 UPI up to 10.4 GT/s
- Intel® C621 chipset
- Up to 6TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 6TB 3DS ECC LRDIMM, DDR4-2933MHz, in 24 DIMM slots; Up to 6TB Intel® Optane™ DC Persistent Memory in memory mode.
- 1 PCI-E 3.0 x16 slot (FH, 10.5" L),5 PCI-E 3.0 x8 slots (FH, 10.5" L),1 PCI-E 3.0 x8 slot (LP),1 PCI-E 3.0 x8 slot (internal LP)
- 2x 10GBase-T LAN ports via Intel X540
- 12 Hot-swap 3.5" drive bays:12 SATA (opt. 8 SAS3 + 4 NVMe/SAS3),Optional 2 hot-swap 2.5" rear drive bays for SSDs;Optional M.2 NVMe and SATA3 ports
- 4 Heavy duty 8cm fans
- 1000W High efficiency (96%),Redundant PSU; Titanium Level



Processor/Cache		Front Panel	
Processor	2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 2 UPI up to 10.4 GT/s	Led's	Power status LED, HDD activity LED,Network activity LEDs,System information (overheat/UID) LED
Chipset	Intel® C621 chipset	Buttons	Power On/Off button,System Reset button
System Memory		Drive Bays	
Memory Capacity	Up to 6TB 3DS ECC RDIMM, DDR4-2933 MHz; Up to 6TB 3DS ECC LRDIMM, DDR4-2933MHz, in 24 DIMM slots;Up to 6TB Intel® Optane™ DC Persistent Memory in memory mode.	HDD bays	12 Hot-swap 3.5" drive bays,12 SATA3 ports by default;Optional 8 SAS3 + 4 NVMe/SAS3
Expansion Slots		M.2	1 M.2 PCI-E 3.0 x4 M-Key NVMe and 1 M.2 M-Key SATA3 via optional riser card RSC-UMR-8, cable CBL-SAST-0538 and plastic stand-off FST-SCRW 0074L (2240/2260/2280/22110),2 M.2 PCI-E 3.0 x4 M-Key NVMe via optional add-on card AOC-SLG3-2 (2260/2280/22110)
PCI-Express	1 PCI-E 3.0 x16 slot (FH, 10.5" L), 5 PCI-E 3.0 x8 slots (FH, 10.5" L),1 PCI-E 3.0 x8 slot (LP),1 PCI-E 3.0 x8 slot (internal LP)	Power Supply	
Integrated On-Board		1000W High efficiency (96%),Redundant PSU; Titanium Level	
SATA	SATA3 (6Gbps); RAID 0, 1, 5, 10	Cooling System	
LAN	2 RJ45 10GBase-T Ethernet LAN ports, 1 RJ45 Dedicated IPMI LAN port	4 Heavy duty 8cm PWM fans	
Add-on Options		Form Factor	
Raid Card	Optional	Form Factor	2U Rackmount
Optical Drive	None	Height	: 3.5" (89mm),
		Width	: 17.2" (437mm),
		Depth	: 28.46" (723mm)
Email : info@tyronesystems.com			
For more/current product information, visit www.tyronesystems.com			