

# Tyrone Camarero Specifications

Camarero DS400TG-14R

## Key features

3D/2D and CAD Applications, Cloud and Virtualization, Oil and Gas Exploration  
Supports 3x double width GPU or 4 single width GPUs; Support for passively cooled GPUs

- 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors. Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 3 UPI up to 10.4 GT/s
- Intel® C621 chipset
- Up to 4TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-2933MHz, in 16 DIMM slots; Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only)
- 4 PCI-E 3.0 x16 (FHFL) slots, 1 PCI-E 3.0 x8 (in x16, LP) slots
- 2 Hot-swap 2.5" SAS/SATA drive bays, 2 Hot-swap 2.5" SAS/SATA/NVMe drive bays
- 1 SIOM for flexible Networking
- 10 Counter rotating fans with optimal fan speed control
- 1600W Redundant Power Supplies Platinum Level (94%)



## Processor/Cache

|           |  |
|-----------|--|
| Processor | 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors. Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 3 UPI up to 10.4 GT/s |
|-----------|--|

## Chipset

|         |                     |
|---------|---------------------|
| Chipset | Intel® C621 chipset |
|---------|---------------------|

## System Memory

|                 |  |
|-----------------|--|
| Memory Capacity | Up to 4TB 3DS ECC RDIMM, DDR4-2933 MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-2933MHz, in 16 DIMM slots; Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only) |
|-----------------|--|

## Expansion Slots

|             |  |
|-------------|--|
| PCI-Express | 4 PCI-E 3.0 x16 (FHFL) slots,<br>1 PCI-E 3.0 x8 (in x16, LP) slots |
|-------------|--|

## Integrated On-Board

|      |                                     |
|------|-------------------------------------|
| SATA | SATA3 (6Gbps) with RAID 0, 1, 5, 10 |
| LAN  | 1 RJ45 Dedicated IPMI LAN port      |

## Add-on Options

|               |          |
|---------------|----------|
| Raid Card     | Optional |
| Optical Drive | None     |

## Front Panel

|                |   |
|----------------|---|
| LED Indicators | Power LED, Hard drive activity LED, Network activity LEDs, System Overheat LED / Fan fail LED / UID LED |
| Buttons        | Power On/Off button, System Reset button  |

## Drive Bays

|          |                            |
|----------|----------------------------|
| HDD bays | 4 Hot-swap 2.5" drive bays |
|----------|----------------------------|

## Power Supply

|   |
|---|
| 1600W Redundant Power Supplies Platinum Level (94%) |
|---|

## Cooling System

|   |
|---|
| 10 Counter rotating fans with optimal fan speed control |
|---|

## Form Factor

|             |                  |
|-------------|------------------|
| Form Factor | 1U Rackmount     |
| Height      | : 1.7" (43mm),   |
| Width       | : 17.2" (437mm), |
| Depth       | : 30.6" (777mm)  |

Email : [info@tyronesystems.com](mailto:info@tyronesystems.com)

For more/current product information, visit

[www.tyronesystems.com](http://www.tyronesystems.com)