

Tyrone Camarero Specifications

Tyrone

Camarero DS400TN-224R4T

Key features

- **Virtualization,Hyperconverge Storage,Cloud Computing,High End Enterprise Server**
- 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 2 UPI up to 10.4 GT/s
- Intel® C621 chipset
- Up to 6TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 6TB 3DS ECC LRDIMM, DDR4-2933MHz, in 24 DIMM slots;Up to 6TB Intel® Optane™ DC Persistent Memory in memory mode.
- 2 PCI-E 3.0 x16 slots (FH, 10.5" L),1 PCI-E 3.0 x8 slot (LP)
- 4 10GBase-T LAN ports with Intel X550
- 24 Hot-swap 2.5" drive bays;24 NVMe (4 hybrid ports - SAS3 via opt. AOC), 2 rear Hot-swap 2.5" drive bays;2 internal M.2 (1 SATA3, 1 NVMe);1 M.2 NVMe port, Optional extra,M.2 NVMe and SATA3 ports
- 4 Heavy duty 8cm PWM fans
- 1600W High efficiency (96%),Redundant PSU; Titanium Level



Processor/Cache

| | |
|-----------|---|
| Processor | 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 2 UPI up to 10.4 GT/s |
|-----------|---|

Chipset

| | |
|---------|---------------------|
| Chipset | Intel® C621 Chipset |
|---------|---------------------|

System Memory

| | |
|-----------------|--|
| Memory Capacity | Up to 6TB 3DS ECC RDIMM, DDR4-2933 MHz; Up to 6TB 3DS ECC LRDIMM, DDR4-2933MHz, in 24 DIMM slots;Up to 6TB Intel® Optane™ DC Persistent Memory in memory mode. |
|-----------------|--|

Expansion Slots

| | |
|-------------|---|
| PCI-Express | 2 PCI-E 3.0 x16 slots (FH, 10.5" L),1 PCI-E 3.0 x8 slot (LP)) |
|-------------|---|

Integrated On-Board

| | |
|------|--|
| SATA | SATA3 (6Gbps); RAID 0, 1, 5, 10 per node |
| LAN | 4 10GBase-T LAN ports,1 RJ45 Dedicated IPMI LAN port |

Add-on Options

| | |
|---------------|----------|
| Raid Card | Optional |
| Optical Drive | None |

Front Panel

| | |
|----------------|---|
| LED Indicators | Power LED,Hard drive activity LED,Network activity LEDs,System Overheat LED / Fan fail LED /UID LED |
|----------------|---|

| | |
|---------|---|
| Buttons | Power On/Off button,System Reset button |
|---------|---|

Drive Bays

| | |
|----------|---|
| HDD Bays | 24 Hot-swap 2.5" drive bays: 24 NVMe (4 hybrid ports - SAS3 via opt. AOC), 2 rear Hot-swap 2.5" SATA drive bays |
| M.2 | 1 M.2 PCI-E 3.0 x4 M-Key NVMe (2240/2260 /2280/22110),1 M.2 M-Key SATA3 via optional cable CBL-SAST-0538 and plastic stand-off FST-SCRW-0074L (2240/2260/2280 /22110),2 M.2 PCI-E 3.0 x4 M-Key NVMe via optional add-on card AOC-SLG3-2M2 (2260/2280/22110) |

Power Supply

| |
|---|
| 1600W High efficiency (96%),Redundant PSU; Titanium Level |
|---|

Cooling System

| |
|---------------------------|
| 4 Heavy duty 8cm PWM fans |
|---------------------------|

Form Factor

| | |
|-------------|--------------------|
| Form Factor | 2U Rackmount |
| Height | : 3.5" (89mm), |
| Width | : 17.2" (437mm), |
| Depth | : 27.76" (705.3mm) |

Email : info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com