

Tyrone Camarero Specifications

Tyrone[®]

Camarero DS400TR-34L

Key features

- 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors. Dual Socket P (LGA 3647) supported, CPU TDP support Up to 140W, 2 UPI up to 10.4 GT/s
- Intel® C621 Chipset
- Up to 2TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-2933MHz, in 8 DIMM slots
- 2 PCI-E 3.0 x16, 3 PCI-E 3.0 x8, 1 PCI-E 3.0 x4 (in x8 slot), M.2 Interface: 1 SATA/PCI-E 3.0 x4, M.2 Form Factor: 2260, 2280 M.2 Key: M-Key
- 1 VGA port
- Intel® C621 controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Dual LAN with Lewisburg Marvell 88E1512 PHY
- 2x 5.25" External HDD Drive Bays & 4x 3.5" Internal HDD Drive Bays
- 1x Rear 12cm (1850 RPM) PWM Fan
- 500W Bronze Level Certified High-Efficiency Power Supply



Processor/Cache	
Processor	2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors. Dual Socket P (LGA 3647) supported, CPU TDP support Up to 140W, 2 UPI up to 10.4 GT/s
Chipset	
Chipset	Intel® C621 Chipset
System Memory	
Memory Capacity	Up to 2TB 3DS ECC RDIMM, DDR4-2933 MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-2933MHz, in 8 DIMM slots
Expansion Slots	
PCI-Express	2 PCI-E 3.0 x16, 3 PCI-E 3.0 x8, 1 PCI-E 3.0 x4 (in x8 slot), M.2 Interface: 1 SATA/PCI-E 3.0 x4, M.2 Form Factor: 2260, 2280 M.2 Key: M-Key
Integrated On-Board	
SATA	Intel® C621 controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10
LAN	2 RJ45 Gigabit Ethernet LAN ports
Add-on Options	
Raid card	Optional
Optical Drive	Optional

Front Panel	
Led's	1 Network Activity LEDs, HDD activity LED, Power Status LED, System Overheat LED
Buttons	Power On/Off button
Drive Bays	
HDD bays	4 x 3.5" fixed drive bay, Optional 4 x 2.5" fixed drive bay
Peripheral Bays	2 x standard 5.25" drive bay, 1 x 3.5" internal fixed drive bay
Power Supply	
500W Bronze Level Certified High-Efficiency Power Supply	
Cooling System	
1x Rear 12cm (1850 RPM) PWM Fan	
Form Factor	
Form Factor	2U Rackmount
Height	: 16.7" (424 mm),
Width	: 7.6" (193 mm),
Depth	: 20.68" (525 mm)
<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	

© Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of Intel Corporation in the U.S and/or other countries
 Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners