

Tyrone Camarero Specifications

Tyrone

Camarero DS400TT-212RL

Key features

HPC, Data Center, Enterprise Server, Financial Analysis, Mission-critical applications

Four hot-pluggable systems (nodes) in a 2U form factor. Each node supports the following:

- 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors.
- Intel C621
- Up to 2TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-2933MHz, in 8 DIMM slots
- 1 PCI-E 3.0 x16 (LP) slot
- Dedicated IPMI 2.0 LAN
- 3 Hot-swap 3.5" SATA3 drive bays
- 2 SATA DOM + 1 SATA/NVMeM.2 (22110/2280)
- Up to 1600W Redundant Power Supplies Titanium Level (96%)



Processor/Cache

Processor 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors.

Chipset

Chipset Intel C621

System Memory

Memory Capacity Up to 2TB 3DS ECC RDIMM, DDR4-2933MHz;
Up to 2TB 3DS ECC LRDIMM, DDR4-2933MHz, in 8 DIMM slots

Expansion Slots

PCI-Express 1 PCI-E 3.0 x16 Low-profile slot

Integrated On-Board

SATA SATA3 (6Gbps); RAID 0, 1, 5 support

LAN 2 RJ45 Gigabit Ethernet LAN ports,
1 RJ45 Dedicated IPMI LAN port

Add-on Options

Raid Card Optional

Optical Drive None

Front Panel

Leds Power status LED, HDD activity LED, Network activity LEDs, Universal Information (UID) LED

Buttons Power On/Off button, UID button

Drive Bays

HDD Bays 3 Hot-swap 3.5" SATA3 HDD tray

Power Supply

1600W Redundant Power Supplies Titanium Level (96%)

Cooling System

1 PCI-E 3.0 x16 Low-profile slot

Form Factor

Form Factor 2U Rackmount

Width 17.25" (438mm)

Height 3.47" (88mm)

Depth 28.5" (724mm)

Email : info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com