

Tyrone Camarero Specifications



Camarero DS400TW-18L

Key features



Web Server, Firewall Apps. Corporate-Wins, DNS, Print, Login. Gateway, provisioning servers. Gateway, provisioning servers Compact Network Appliance, Cloud Computing

- 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors. Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 2 UPI up to 10.4 GT/s
- Intel® C621 chipset
- Up to 3TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 3TB 3DS ECC LRDIMM, DDR4-2933MHz, in 12 DIMM slots; Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only)
- 2 PCI-E 3.0 x16 (FHHL) slots, 1 PCI-E 3.0 x8 (LP) slot, 1 PCI-E 3.0 x16 for Add-on-Module, 1 PCI-E M.2 SSD slot
- 8 Hot-swap 2.5" SAS/SATA drive bays
- Optional 1 slim DVD-ROM drive bay
- 2 1GbE LAN ports via Intel® X722
- 1 VGA, 4 USB 3.0 (rear)
- 2 SuperDOM (Disk on Module) ports
- 600W Multi Output Power Supply, Platinum Level High-efficiency



Processor/Cache		Front Panel	
Processor	2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors. Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 2 UPI up to 10.4 GT/s	LED Indicators	Power status LED, HDD activity LED, Network activity LEDs, Universal Information (UID) LED
Chipset	Intel® C621 chipset	Buttons	Power On/Off button, UID button
System Memory		Drive Bays	
Memory Capacity	Up to 3TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 3TB 3DS ECC LRDIMM, DDR4-2933MHz, in 12 DIMM slots; Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only)	HDD Bays	8 Hot-swap 2.5" SAS/SATA drive bays
Expansion Slots		Peripheral Bays	1 Slim DVD-ROM drive bay (optional)
PCI-Express	2 PCI-E 3.0 x16 (FHHL) slots, 1 PCI-E 3.0 x8 (LP) slot, 1 PCI-E 3.0 x16 for Add-on-Module, 1 PCI-E M.2 SSD slot	Power Supply	
Integrated On-Board		600W Multi Output Power Supply, Platinum Level High-efficiency	
SATA	SATA3 (6Gbps); RAID 0, 1, 5, 10	Cooling System	
LAN	2 RJ45 Gigabit Ethernet ports, 1 RJ45 Dedicated IPMI LAN port	4 Counter-rotating 4cm PWM fans, 2 fans or cooling AOC	
Add-on Options		Form Factor	
Raid Card	Optional	Form Factor	1U Rackmount
Optical Drive	Optional	Height	: 1.7" (43mm),
		Width	: 17.2" (437mm),
		Depth	: 23.5" (597mm)
		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	

© Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of Intel Corporation in the U.S. and/or other countries.
 © Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners.