

Tyrone Camarero Specifications



Camarero DS400TW-28RL

Key features

Web Server, Firewall Apps, Corporate-Wins, DNS, Print, Login, Gateway, provisioning servers, Compact Network Appliance, Cloud Computing

- 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors. Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 2 UPI up to 10.4 GT/s
- Intel® C621 chipset
- Up to 3TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 3TB 3DS ECC LRDIMM, DDR4-2933MHz, in 12 DIMM slots; Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only)
- 4 PCI-E 3.0 x8 (FHHL) slots, 2 PCI-E 3.0 x8 (LP) slots, 1 PCI-E 3.0 x16 for Add-on-Module, 1 PCI-E M.2 SSD slot
- 8 Hot-swap 3.5" SAS/SATA drive bays with SGPIO, 2 Fixed 3.5" drive bays
- 1 Slim DVD-ROM drive bay (optional)
- 2x 1GbE LAN ports via Intel C621
- 1 VGA, 4 USB 3.0 (rear)
- M.2 support
- 1000W Redundant Power Supplies Titanium Level (96% Efficiency)



Processor/Cache	
Processor	2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors. Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 2 UPI up to 10.4 GT/s
Chipset	
Chipset	Intel® C621 chipset
System Memory	
Memory Capacity	Up to 3TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 3TB 3DS ECC LRDIMM, DDR4-2933MHz, in 12 DIMM slots; Up to 2TB Intel® Optane DC Persistent Memory in memory mode (Cascade Lake only)
Expansion Slots	
PCI-Express	4 PCI-E 3.0 x8 (FHHL) slots, 2 PCI-E 3.0 x8 (LP) slots, 1 PCI-E 3.0 x16 for Add-on-Module, 1 PCI-E M.2 SSD slot
Integrated On-Board	
SATA	SATA3 (6Gbps); RAID 0, 1, 5, 10
LAN	2 RJ45 Gigabit Ethernet ports, 1 RJ45 Dedicated IPMI LAN port
Add-on Options	
Raid Card	Optional
Optical Drive	Optional

Front Panel	
LED Indicators	Power status LED, HDD activity LED, Network activity LEDs, Universal Information (UID) LED
Buttons	Power On/Off button, UID button
Drive Bays	
HDD Bays	8 Hot-swap 3.5" SAS/SATA drive bays with SGPIO, 2 Fixed 3.5" drive bays
Peripheral Bays	1 Slim DVD-ROM drive (optional)
Power Supply	
1000W Redundant Power Supplies Titanium Level (96% Efficiency)	
Cooling System	
3 Heavy duty 8cm fans with PWM fan speed control	
Form Factor	
Form Factor	2U Rackmount
Height	: 3.5" (89mm),
Width	: 17.2" (437mm),
Depth	: 25.5" (648mm)
<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit www.tyronesystems.com</p>	