

Tyrone Camarero Specifications



Camarero DS400TWN-110RT

Key features



- Web Firewall Apps, Corporate-Wins, DNS, Print, Login, Gateway, provisioning servers, Compact Network Appliance, Cloud Computing
- 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors. Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 2 UPI up to 10.4 GT/s
- Intel® C622 chipset
- Up to 3TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 3TB 3DS ECC LRDIMM, DDR4-2933MHz, in 12 DIMM slots; Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only).
- 2 PCI-E 3.0 x16 (FHHL) slots, 1 PCI-E 3.0 x8 (LP) slot, 1 PCI-E 3.0 x16 for Add-on-Module, 1 PCI-E M.2 SSD slot
- 10 Hot-swap 2.5" SAS/SATA HDD bays (default 8 SATA3, 2 NVMe or SATA3)
- 2x 10GBase-T LAN ports via Intel® X722
- 1 VGA, 6 USB 3.0 (4 rear, 2 front)
- 2 SuperDOM (Disk on Module) ports
- 750W Redundant Power Supplies Platinum Level High-efficiency



Processor/Cache	
Processor	2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors. Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 2 UPI up to 10.4 GT/s
Chipset	
Chipset	Intel® C622 chipset
System Memory	
Memory Capacity	Up to 3TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 3TB 3DS ECC LRDIMM, DDR4-2933MHz, in 12 DIMM slots; Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only).
Expansion Slots	
PCI-Express	2 PCI-E 3.0 x16 (FHHL) slots, 1 PCI-E 3.0 x8 (LP) slot, 1 PCI-E 3.0 x16 for Add-on-Module, 1 PCI-E M.2 SSD slot
Integrated On-Board	
SATA	8 SATA3 (6 Gbps) ports and 2 NVMe/SATA3 hybrid ports, RAID 0, 1, 5, 10
LAN	2 RJ45 10GBase-T ports, 1 RJ45 Dedicated IPMI LAN port
Add-on Options	
Raid Card	Optional
Optical Drive	None

Front Panel	
LED Indicators	Power LED, Hard drive activity LED, Network activity LEDs, Universal Information (UID) LED
Buttons	Power On/Off button, UID button
Drive Bays	
HDD Bays	10 Hot-swap 2.5" SAS/SATA HDD bays (default 8 SATA3, 2 NVMe or SATA3)
Power Supply	
750W Redundant Power Supplies Platinum Level High-efficiency	
Cooling System	
4 Counter-rotating 4cm PWM fans, 2 fans or AOC cooling	
Form Factor	
Form Factor	1U Rackmount
Height	: 1.7" (43mm),
Width	: 17.2" (437mm),
Depth	: 23.5" (597mm)
<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	

Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of Intel Corporation in the U.S. and/or other countries. Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners.