

Tyrone Camarero Specifications



Camarero DS400TWN-212RTL

Key features

- **Web Server, Firewall Apps, Corporate-Wins, DNS, Print, Login, Gateway, provisioning servers, Compact Network Appliance, Cloud Computing**
- 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors. Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 2 UPI up to 10.4 GT/s
- Intel® C622 chipset
- Up to 3TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 3TB 3DS ECC LRDIMM, DDR4-2933MHz, in 12 DIMM slots; Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only).
- 1 PCI-E 3.0 x16 (FHHL) slots, 2 PCI-E 3.0 x8 (FHHL) slots,
- 2 PCI-E 3.0 x8 (LP) slots, 1 PCI-E 3.0 x16 for Add-on-Module, 1 PCI-E M.2 SSD slot
- 12 Hot-swap 3.5" SAS/SATA drive bays with SES2 and Mini-i-Pass (SFF 8087) connectivity
- 2x 10GBase-T ports via Intel C622
- 1 VGA, 4 USB 3.0 (rear)
- 1200W Redundant Power Supplies Titanium Level (96% Efficiency)



Processor/Cache		Front Panel	
Processor	2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors. Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 2 UPI up to 10.4 GT/s	LED Indicators	Power status LED, HDD activity LED, Network activity LEDs, Universal Information (UID) LED
Buttons		Buttons	Power On/Off button, UID button
Chipset		Drive Bays	
Chipset	Intel® C622 chipset	HDD Bays	12 Hot-swap 3.5" SAS/SATA drive bays with SES2 and Mini-i-Pass (SFF 8087) connectivity
System Memory		Power Supply	
Memory Capacity	Up to 3TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 3TB 3DS ECC LRDIMM, DDR4-2933MHz, in 12 DIMM slots; Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only).	1200W Redundant Power Supplies Titanium Level (96% Efficiency)	
Expansion Slots		Cooling System	
PCI-Express	1 PCI-E 3.0 x16 (FHHL) slots, 2 PCI-E 3.0 x8 (FHHL) slots, 2 PCI-E 3.0 x8 (LP) slots, 1 PCI-E 3.0 x16 for Add-on-Module, 1 PCI-E M.2 SSD slot	3 High-performance 8cm PWM fans	
Integrated On-Board		Form Factor	
SATA	SATA3 (6Gbps); RAID 0, 1, 5, 10	Form Factor	2U Rackmount
LAN	2 RJ45 10GBase-T ports, 1 RJ45 Dedicated IPMI LAN port	Height	: 3.5" (89mm),
		Width	: 17.2" (437mm),
		Depth	: 25.5" (648mm)
Add-on Options		Email : info@tyronesystems.com For more/current product information, visit www.tyronesystems.com	
Raid Card	Optional		
Optical Drive	None		

Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of Intel Corporation in the U.S. and/or other countries. Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners.