

# Tyrone Camarero Specifications

Camarero DS4A0TR-28R

# Tyrone

## Key features

- EATX Server Board with dual Xeon Scalable processors
- Intel C621
- DDR4 2666 MHz RDIMM up to 768 GB (24 DIMMs)
- 5 PCIe x16 (Gen3) and one PCIe x8 (Gen3) for three double-deck cards
- LAN1: Intel I210AT , LAN2: Intel I210AT, 10/100/1000 Mbps, 2 x RJ-45
- 10 SATA3 and six USB3.0 ports
- One M.2 2280 (SATA / PCIe compatible)
- 0 ~ 40 °C ambient operation temperature range
- Supports IPMI 2.0
- 8x 3.5" Hot-swap SAS3/ SATA Drive Bays & 2x Fixed 3.5" Drive Bays
- 3 x 80mm heavy duty fan(s) with PWM fan(s) speed control
- 800/1000W Redundant Titanium Single Output Power Supply W/PMbus



## Processor/Cache

Processor EATX Server Board with dual Xeon Scalable processors

## Chipset

Chipset Intel C621

## System Memory

Memory Capacity DDR4 2666 MHz RDIMM up to 768 GB (24 DIMMs)

## Expansion Slots

PCI-Express 5 PCIe x16 (Gen3) and one PCIe x8 (Gen3) for three double-deck cards

## Integrated On-Board

SATA 10 x SATAIII (RAID 0,1,5,10)  
LAN LAN1: Intel I210AT,LAN2: Intel I210AT  
IPMI Supports IPMI 2.0

## Add-on Options

Raid Card Optional  
Optical Drive Optional

## Front Panel

Led's 2 Network Activity LEDs,HDD activity LED,Power Status LED,Power Fail LED,System Information LED

Buttons Power On/Off button,System Reset button

## Drive Bays

HDD Bays 8 x 3.5" hot-swap SAS3/SATA drive bay, 2 x 3.5" fixed drive bay

Peripheral Drives Optional 1 x slim DVD-ROM drive bay, Optional 2 x USB 2.0 ports,Optional 1 x COM port tray,Optional 2 x USB 3.0 ports

## Power Supply

800/1000W Redundant Titanium Single Output Power Supply W/PMbus

## Cooling System

3 x 80mm heavy duty fan(s) with PWM fan(s) speed control

## Form Factor

Form Factor : 2U Rackmount  
Height : 3.5" (89 mm)  
Width : 17.2" (437 mm)  
Depth : 25.5" (647 mm)

Email : [info@tyronesystems.com](mailto:info@tyronesystems.com)

For more/current product information, visit  
[www.tyronesystems.com](http://www.tyronesystems.com)