

Tyrone Camarero Specifications

Camarero DS4A0TR-48L

Key features

- EATX Server Board with dual Xeon Scalable processors
- Intel C621
- DDR4 2666 MHz RDIMM up to 768 GB (24 DIMMs)
- 5 PCIe x16 (Gen3) and one PCIe x8 (Gen3) for three double-deck cards
- LAN1: Intel I210AT , LAN2: Intel I210AT, 10/100/1000 Mbps, 2 x RJ-45
- 10 SATA3 and six USB3.0 ports
- One M.2 2280 (SATA / PCIe compatible)
- 0 – 40 °C ambient operation temperature range
- 8 x 3.5" hot-swap SAS/SATA
- 4 x 5000 RPM Hot-swap PWM Cooling Fans
- 500/1200W high efficiency Power Supply



Processor/Cache

Processor EATX Server Board with dual Xeon Scalable processors

Chipset

Chipset Intel C621

System Memory

Memory Capacity DDR4 2666 MHz RDIMM up to 768 GB (24 DIMMs)

Expansion Slots

PCI-Express 5 PCIe x16 (Gen3) and one PCIe x8 (Gen3) for three double-deck cards

Integrated On-Board

SATA 10 x SATAIII (RAID 0,1,5,10)

LAN LAN1: Intel I210AT,LAN2: Intel I210AT

Add-on Options

Raid Card Optional

Optical Drive Optional

Front Panel

LED 2 Network Activity LEDs,Fan Fail/System Over Heat LED,HDD activity LED, Power Status LED,Unit Identification (UID) LED

Buttons Power On/Off button,System Reset Button

Drive Bays

HDD Drives 8 x 3.5" hot-swap SAS/SATA

Peripheral Drives 3 x standard 5.25" drive bay

Power Supply

500/1200W high efficiency Power Supply

Cooling System

4 x 5000 RPM Hot-swap PWM Cooling Fans

Form Factor

Form Factor 4U Rackmount

Height: 17.8" (452 mm),

Width: 7" (178 mm),

Depth: 25.5" (647 mm)

Email : info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com