

# Tyrone Camarero Specifications



## Camarero DSA70TR-224R

### Key features

- Dual AMD EPYC™ 7001/7002\* series Processors (\*Board revision 2.x required), Socket SP3, Up to 240W TDP, Up to 32 Cores, Up to 64 Cores (Board revision 2.x required)
- System on Chip
- 16 DIMM sockets, Supports up to 2TB Registered ECC DDR4 2666MHz SDRAM in 16 DIMMs  
Supports up to 4TB Registered ECC DDR4 3200MHz SDRAM (Board revision 2.x required)
- 8-channel memory bus, DDR4 2666 MHz Registered ECC, 288-pin gold-plated DIMMs  
DDR4 3200 MHz Registered ECC, 288-pin gold-plated DIMMs (Board revision 2.x required)"
- 3 PCI-E 3.0 x8, 2 PCI-E 3.0 x16, Interface: 1 SATA/PCI-E 3.0 x2  
(Platform with EPYC 7002 processor only supports PCI-E type M.2 module), Form factor: 2280, 22110, Key: M-key"
- 10 SATA3, 1 M.2, 2 SATA DOM
- Dual Gigabit Ethernet LAN Ports
- ASPEED AST2500 BMC graphics
- Up to 2 USB 3.0 ports, Up to 4 USB 2.0 ports
- 8 4-pin PWM Fan & Speed control
- 24 x 2.5" hot-swap SAS/SATA drive bay, optional 2 x 2.5" hot-swap drive bay
- 3 x 8cm high-performance PWM fan(s) Optional 5 x 6cm 4pin high performance fan(s)
- 1200W/1000W Titanium Power Supply W/PMbus W76xL336xH40mm



Processor/Cache	
Processor	Dual AMD EPYC™ 7001/7002* series Processors (*Board revision 2.x required), Socket SP3, Up to 240W TDP, Up to 32 Cores, Up to 64 Cores (Board revision 2.x required)
Chipset	
Chipset	System on Chip
System Memory	
Memory Capacity	16 DIMM sockets, Supports up to 2TB Registered ECC DDR4 2666MHz SDRAM in 16 DIMMs Supports up to 4TB Registered ECC DDR4 3200MHz SDRAM (Board revision 2.x required) 8-channel memory bus, DDR4 2666 MHz Registered ECC, 288-pin gold-plated DIMMs DDR4 3200 MHz Registered ECC, 288-pin gold-plated DIMMs (Board revision 2.x required)
Expansion Slots	
PCI-Express	3 PCI-E 3.0 x8, 2 PCI-E 3.0 x16, Interface: 1 SATA/PCI-E 3.0 x2 (Platform with EPYC 7002 processor only supports PCI-E type M.2 module), Form factor: 2280, 22110, Key: M-key
Integrated On-Board	
SATA	10 SATA3 (6 Gbps) ports
LAN:	2 RJ45 Gigabit Ethernet LAN ports, 1 RJ45 Dedicated IPMI LAN port
Add-on Options	
Raid Card	Optional
Optical Drive	None

Front Panel	
LED s	2 Network Activity LEDs, HDD activity LED, Power Status LED, Power Fail LED, System Information LED
Buttons	Power On/Off button, System Reset button
Drive Bays	
HDD Bays	24 x 2.5" hot-swap SAS/SATA drive bay, optional 2 x 2.5" hot-swap drive bay
Power Supply	
	1200W/1000W Titanium Power Supply W/PMbus W76xL336xH40mm
Cooling System	
	3 x 8cm high-performance PWM fan(s), Optional 5 x 6cm 4pin high performance fan(s)
Form Factor	
Form Factor	2U Rackmount
Dimensions:	Height : 3.5" (89 mm), Width : 17.2" (437 mm), Depth : 24.8" (630 mm)
<p><b>Email : <a href="mailto:info@tyronesystems.com">info@tyronesystems.com</a></b></p> <p><b>For more/current product information, visit</b></p> <p><b><a href="http://www.tyronesystems.com">www.tyronesystems.com</a></b></p>	