

Tyrone Camarero Specifications



Camarero IDI100C2R-28

Key features

- 3rd Generation Intel® Xeon® Scalable Processors Socket-P4, 270 W
- Intel® C621A Chipset
- DDR4 (RDIMM), 3DS-RDIMM, Load Reduced DDR4 (LRDIMM), 3DS-LRDIMM, Intel® Optane™ persistent memory 200 series
Max DIMMs 32, Max Memory Size (dependent on memory type) 12 TB"
- Riser Slot 1: Lanes 32, Riser Slot 2: Lanes 32, Riser Slot 3: Lanes 16
- 8 Hot-Swap 2.5" SSD,
optional 16 and 24 bays
- 10 SATA Ports, RAID 0/1/5/10, 8 Integrated SAS Ports
- Three USB 3.0 on the back panel, One USB 3.0 + one USB 2.0 on the front panel,
One USB 2.0 internal Type-A
- 1300W (Titanium) Redundant Power Supply, optional upgrade to 1600W (Titanium)
/2100W (Platinum) Redundant Power Supply.
- 2U Rackmount



| Processor/Cache | | Add-on Options | |
|--------------------|---|--|---|
| Processor | 3rd Generation Intel® Xeon® Scalable Processors Socket-P4, 270 W | Optical Drive | None |
| Chipset | | Drive Bays | |
| Chipset | Intel® C621A | HDD Bays | 8 Hot-Swap 2.5" SSD, optional 16 and 24 bays |
| System Memory | | Power Supply | |
| Memory Capacity | DDR4 (RDIMM), 3DS-RDIMM, Load Reduced DDR4 (LRDIMM), 3DS-LRDIMM, Intel® Optane™ persistent memory 200 series Max DIMMs 32, Max Memory Size (dependent on memory type) 12 TB" | 1300W (Titanium) Redundant Power Supply, optional upgrade to 1600W (Titanium) /2100W (Platinum) Redundant Power Supply. | |
| Expansion Slots | | Form Factor | |
| PCI-Express | Riser Slot 1: Lanes 32, Riser Slot 2: Lanes 32, Riser Slot 3: Lanes 16 | Form Factor | 2U Rackmount |
| Integrated Onboard | | Dimensions | 770 x 446 x 87 mm |
| SATA | 10 SATA Ports, RAID 0/1/5/10, 8 Integrated SAS Ports | Email : info@tyronesystems.com For more/current product information, visit www.tyronesystems.com | |
| USB | Three USB 3.0 on the back panel, One USB 3.0 + one USB 2.0 on the front panel, One USB 2.0 internal Type-A | | |