

Tyrone Camarero Specifications

Tyrone

Camarero JSG00R-212

Key features

- Dual I/O modules per enclosure
- Three universal x4 12 Gb/s mini-SAS HD connectors (SFF-8644) per I/O module
- CLI via RS232 and 100Base-T port SES via SAS SFF-8644 ports
- Dual host-connected enclosure with a maximum expanded configuration of 12 enclosures for a total of 144 drives
- Dual port 12 Gb/s and 6 Gb/s SAS drives
- 12 Drives
- 580W Dual Power supply



Host/Expansion Interface

Three universal x4 12 Gb/s mini-SAS HD connectors (SFF-8644) per I/O module

Drive Bays

12 Drive bays

Environmental/Temperature Ranges

Operating/Non-operating Altitude : 0 m to 3,000 m (0 ft to 10,000 ft)/-300 m to 12,192 m (-1,000 ft to 40,000 ft)

Operating/Non-operating Temperature : ASHRAE A3, 5°C to 40°C (41°F to 104°F), derate 1°C/175m above 900m, 20°C/hr max rate of change / -40°C to 70°C (-40°F to 158°F)

Operating/Non-operating Humidity : -12°C DP and 10% RH to 21°C DP and 80% RH, max DP 21°C / 5% to 100% non-condensing

Operating/Non-operating Shock : 5 Gs, 10ms, half sine pulses/15 Gs, 10ms, half sine pulses

Operating/Non-operating Vibration : 0.21 Gs rms (5-500Hz) / 1.04 Gs rms (2-200Hz)

Power Supply

580W Dual Power supply

Form Factor

Form Factor 2U rackmount

Dimensions Height: 88.9 mm / 3.5 in (2 EIA units)
Width: 483 mm / 19 in (IEC rack compliant)
Depth: 630 mm / 24.8 in
Weight: 26 kg / 52.7 lb (with drives)

Email : info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com