

Tyrone Camarero Specifications

Tyrone®

Camarero SDI100C2R-28

Key features

Virtualization, Enterprise Server, Data Center Optimized, Application and data serving, Model analysis, Compute Intensive Applications

- Dual Socket P+ (LGA-4189), 3rd Gen Intel® Xeon® Scalable processors, Support CPU TDP 270W
- Intel® C621A
- Memory Capacity: 18 DIMM slots, UP to 4TB: PMem and DRAM, Memory Type: 3200MHz ECC LRDIMM/RDIMM DDR4, Intel® Optane™ persistent memory 200 series
- 4 PCI-E 4.0 x16 Low Profile (LP), 2 PCI-E 4.0 x8 Low Profile (LP)
- Dual 10GbE LAN ports
- 8x 3.5" SATA drive bays
- 3 heavy duty fans with optimal fan speed control
- 600W/650W/740W/800W/1000W/1200W Redundant Power Supply



Processor/Cache	
Processor	Dual Socket P+ (LGA-4189), 3rd Gen Intel® Xeon® Scalable processors, Support CPU TDP 270W
Chipset	
Chipset	Intel® C621A
System Memory	
Memory Capacity	18 DIMM slots, UP to 4TB: PMem and DRAM, Memory Type: 3200MHz ECC LRDIMM/RDIMM DDR4, Intel® Optane™ persistent memory 200 series
Expansion Slots	
PCI-Express	4 PCI-E 4.0 x16 Low Profile (LP), 2 PCI-E 4.0 x8 Low Profile (LP)
Integrated Onboard	
Network Connectivity	2x 10GbE port(s)
LAN	1 dedicated IPMI LAN port
Add-on Options	
Raid Card	None
Optical Drive	Optional
Front Panel	
LEDs	HDD activity, Network activity, Power status, System information (overheat/UID)
Buttons	Power On/Off , System Reset
Drive Bays	
HDD Bays	Hot-swap 8x 3.5" hot-swap fixed optional drive bays, 1 M.2 NVMe
Peripheral Drives	1x slim DVD drive bays (optional)
Power Supply	
600W/650W/740W/800W/1000W/1200W Redundant Power Supply	
Cooling System	
3 heavy duty fans with optimal fan speed control	
Form Factor	
Form Factor	2U Rackmount
Dimensions	Height : 3.5" (89mm), Width : 17.2" (437mm), Depth : 25.5" (647mm)
Email : info@tyronesystems.com	
For more/current product information, visit www.tyronesystems.com	