

Tyrone Camarero Specifications

Tyrone[®]

Camarero SDI100C3A-34

Key features

Rendering, CAD, Multimedia/Digital Content creation, Engineering/scientific research

- Dual Socket P+ (LGA-4189), 3rd Gen Intel® Xeon® Scalable processors Support CPU TDP 270W , Up to 40C/80T; Up to 60MB Cache
- Intel® C621A
- Up to 4TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-3200MHz, Up to 6TB Intel® Optane™ Persistent Memory, DDR4-3200MHz, in 16 DIMM slots; Up to 6TB Intel® Optane™ DC Persistent Memory in memory mode.
- 5 PCI-E 4.0 x16, 1 PCI-E 4.0 x8, 2 NVMe M.2 slots
- Intel® C621A controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Dual LAN with Intel® i210 Gigabit Ethernet Controller
- 1 VGA D-Sub Connector port
- 4 x 3.5" fixed drive bay, Optional 4 x 2.5" fixed drive bay
- 2x 12cm heavy duty fans with optimal fan speed control
- 900W/1200W High-Efficiency Power Supply



SC732D4 front I/O:
2x USB 3.0 ports,
2x USB 2.0 ports,
2x HD/AC97 Audio ports



| Processor/Cache | |
|--------------------|---|
| Processor | Dual Socket P+ (LGA-4189), 3rd Gen Intel® Xeon® Scalable processors Support CPU TDP 270W ,Up to 40C/80T; Up to 60MB Cache |
| Chipset | |
| Chipset | Intel® C621A |
| System Memory | |
| Memory Capacity | Up to 4TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-3200MHz, Up to 6TB Intel® Optane™ Persistent Memory, DDR4-3200MHz, in 16 DIMM slots;Up to 6TB Intel® Optane™ DC Persistent Memory in memory mode. |
| Expansion Slots | |
| PCI-Express | 5 PCI-E 4.0 x16, 1 PCI-E 4.0 x8, 2 NVMe M.2 slots |
| Integrated Onboard | |
| SATA | SATA3 (6Gbps); RAID 0/1/5/10 support |
| LAN | 2 RJ45 1GbE (IPMI Shared on LAN port1) |
| Add-on Options | |
| Raid Card | Optional |
| Optical Drive | Optional |

| Front Panel | |
|---|--|
| LEDs | HDD activity, Network activity LED |
| Buttons | Power On/Off Button |
| Drive Bays | |
| HDD Bays | 4 x 3.5" fixed drive bay, Optional 4 x 2.5" fixed drive bay |
| Peripheral Bay | 2x 5.25" drive bays ,1 x 3.5" internal fixed drive bay |
| Power Supply | |
| | 900W/1200W High-Efficiency Power Supply |
| Cooling System | |
| | 2x 12cm heavy duty fans with optimal fan speed control |
| Form Factor | |
| Form Factor | Mid Tower |
| Dimensions: | Height : 16.7" (424mm), Width : 7.6" (193mm), Depth : 20.68" (525.3mm) |
| <p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p> | |