

Tyrone Camarero Specifications

Tyrone

Camarero SS0iTR-45T

Key features

- 10th Generation Intel® Core™ i9/Core™ i7/Core™ i5/Core™ i3/Pentium®/Celeron® Processor Single Socket LGA-1200 (Socket H5) supported, CPU TDP support Up to 140W TDP
- Intel® Z490
- Up to 128GB Unbuffered non-ECC UDIMM, DDR4-2933MHz, in 4 DIMM slots
2933 MHz to 4000+MHz(OC) in four 288-pin memory slots.
- 4 PCI-E 3.0 x16 slots (16/NA/16/NA or 8/8/8/8), 1 PCI-E 3.0 x1
M.2 : M.2 Interface: 2 PCI-E 3.0 x4, RAID 0 & 1 and 1 CNVi, RAID 0 & 1, Form Factor: 2260/2280/22110
Key: M-Key , E-Key, RSTe software raid; M.2-E1 port pre-installed one Intel Wi-Fi 6(802.11ax)+BT5.1 module
2 M.2 M-Key PCI-E 3.0 x4, 2260/2280/22110
- 1 DP (DisplayPort) port, 1 HDMI port, DP version 1.4, HDMI version 2.0a
- Single LAN with Intel® single Ethernet PHY i219V, Single LAN with Aquantia® AQC107 10G Ethernet Controller
- External: 5.25" x 4, 3.5" x 1; Internal: 3.5" x 5 or 2.5" x 5
- Front:120 x 25 mm x1 PWM Fan, Rear: 120 x 25 mm x1 PWM Fan
- 500 / 1200W Single power supply ,80 Plus platinum



Processor/Cache

Processor 10th Generation Intel® Core™ i9/Core™ i7/Core™ i5/
Core™ i3/Pentium®/Celeron® Processor
Single Socket LGA-1200 (Socket H5) supported,
CPU TDP support Up to 140W TDP

Chipset

Chipset Intel® Z490

System Memory

Memory Capacity Up to 128GB Unbuffered non-ECC UDIMM,
DDR4-2933MHz, in 4 DIMM slots
2933 MHz to 4000+MHz(OC) in four
288-pin memory slots.

Expansion Slots

PCI-Express 4 PCI-E 3.0 x16 slots (16/NA/16/NA or 8/8/8/8),
1 PCI-E 3.0 x1 M.2 : M.2 Interface: 2 PCI-E
3.0 x4, RAID 0 & 1 and 1 CNVi, RAID 0 & 1,
Form Factor: 2260/2280/22110
Key: M-Key , E-Key, RSTe software raid;
M.2-E1 port pre-installed one Intel
Wi-Fi 6(802.11ax)+BT5.1 module 2 M.2
M-Key PCI-E 3.0 x4, 2260/2280/22110

Integrated Onboard

SATA 4 SATA3 (6Gbps) ports

LAN 1 RJ45 Gigabit Ethernet LAN ports,
1 RJ45 10GBase-T ports

Add-on Options

Raid Card Optional

Optical Drive None

Front Panel

Front Panel Front Control Panel Power Switch, System Reset,
USB 3.0 x 2

Buttons Power On/Off button

Drive Bays

HDD Bays External: 5.25" x 4, 3.5" x 1;
Internal: 3.5" x 5 or 2.5" x 5

Power Supply

500 / 1200W Single power supply ,80 Plus platinum

Cooling System

Front:120 x 25 mm x1 PWM Fan,
Rear: 120 x 25 mm x1 PWM Fan

Form Factor

Form Factor 5U Rackmount

Dimensions: 560 x 200 x 430 mm (22" x 7.9" x 16.9")

Email : info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com