

# Tyrone Camarero Specifications

## Camarero SS400TR-310

### Key features

- Intel® Xeon® W-2100 Processors, Intel® Xeon® W-2200 Processors, Single Socket LGA-2066 (Socket R4) supported, CPU TDP supports Up to 165W TDP
- Intel® C422
- Up to 256GB Registered ECC RDIMM, DDR4-2666MHz;  
Up to 512GB Registered ECC LRDIMM, in 8 DIMM slots
- 3 PCI-E 3.0 x16, 1 PCI-E 3.0 x4, 3xPCI-E3.0 x16 Slots(8/16/16 (Skylake-W 48 lanes), 1xPCI-E3.0x4 slots, M.2 Interface: 2 PCI-E 3.0 x4, M.2 Form Factor: 22110, M.2 Key: M-Key (RAID 0,1 support), M-Key for SSD and Optane(up to Intel POR). Intel VROC licence kit is needed to enable RAID, U.2 Interface: 2 PCI-E 3.0 x4
- Intel® C422 controller for 6 SATA3 (6 Gbps) ports; RAID 0,1,5,10, iRST enabled, only SATA2 to SATA5 support RAID.
- Single LAN with Intel® PHY I219LM LAN controller, Single LAN with Aquantia 5G LAN chip AQC108
- 6 x 3.5" fixed drive bay, 4 x 2.5" fixed drive bay
- 2 x 12cm front cooling fan(s), 1 x 12cm rear exhaust fan(s)
- 750W 80PLUS Gold Fully-Modular Power Supply

# Tyrone



### Processor/Cache

Processor	Intel® Xeon® W-2100 Processors, Intel® Xeon® W-2200 Processors, Single Socket LGA-2066 (Socket R4) supported, CPU TDP supports Up to 165W TDP
-----------	---

### Chipset

Chipset	Intel® C422
---------	-------------

### System Memory

Memory Capacity	Up to 256GB Registered ECC RDIMM, DDR4-2666MHz; Up to 512GB Registered ECC LRDIMM, in 8 DIMM slots
-----------------	---

### Expansion Slots

PCI Express	3 PCI-E 3.0 x16, 1 PCI-E 3.0 x4, 3xPCI-E3.0 x16 Slots(8/16/16 (Skylake-W 48 lanes), 1xPCI-E3.0x4 slots, M.2 Interface: 2 PCI-E 3.0 x4 M.2 Form Factor: 22110, M.2 Key: M-Key (RAID 0,1 support), M-Key for SSD and Optane (up to Intel POR). Intel VROC licence kit is needed to enable RAID. U.2 Interface: 2 PCI-E 3.0 x4
-------------	---

### Integrated On-Board

SATA	Intel® C422 controller for 6 SATA3 (6 Gbps) ports; RAID 0,1,5,10, iRST enabled, only SATA2 to SATA5 support RAID
------	--

### Add-on Options

Raid	Optional
Optical Drive	Optional

### Front Panel

LED	HDD activity LED, Power Status LED
Buttons	Power On/Off button, System Reset button

### Drive Bays

HDD Bays	6 x 3.5" fixed drive bay, 4 x 2.5" fixed drive bay
Peripheral Bays	2 x standard 5.25" drive bay

### Power Supply

750W 80PLUS Gold Fully-Modular Power Supply
---

### Cooling System

2 x 12cm front cooling fan(s), 1 x 12cm rear exhaust fan(s)
---

### Form Factor

Form Factor	Mid Tower
Dimensions	(L x W x H) 140 x 150 x 86 mm

Email : [info@tyronesystems.com](mailto:info@tyronesystems.com)

For more/current product information, visit  
[www.tyronesystems.com](http://www.tyronesystems.com)