

Tyrone Camarero Specifications

Tyrone

Camarero SS400TR-34

Key features

- **High Performance Workstation**
- **Designed for 2D/3D Content Creation**
- Single Socket R4 (LGA 2066) supports, Intel® Xeon® W-2200 processor, Intel® Xeon® W-2100 processor.
- Intel® C422 chipset
- Up to 256GB Registered ECC RDIMM, DDR4-2666MHz; Up to 512GB Registered ECC LRDIMM, in 8 DIMM slots
- 3 PCI-E 3.0 x16 (8/16/16, 48 lanes-support for two double width GPUs), 1 PCI-E 3.0 x4, M.2 Interface: 2 PCI-E 3.0 x4, M.2 Form Factor: 22110/2280, M.2 Key: M-Key (RAID 0,1 support-with optional Upgrade to NVMe controller)
- U.2 Interface: 2 PCI-E 3.0 x4
- ALC 1220 7.1 HD Audio, 1 COM, 2 GbE LAN, 2 USB 3.0 (front)
- 4 internal 3.5" drive bays(Optional Upgrade to 12 HDD Bays with 4 x Hot Swap bays)
- 668W/900W/1200W High Efficiency Power Supply



| Processor/Cache | |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Processor | Single Socket R4 (LGA 2066) supports, Intel® Xeon® W-2200 processor, Intel® Xeon® W-2100 processor. |
| Chipset | |
| Chipset | Intel® C422 chipset |
| System Memory | |
| Memory Capacity | Up to 256GB Registered ECC RDIMM, DDR4-2666MHz; Up to 512GB Registered ECC LRDIMM, in 8 DIMM slots |
| Expansion Slots | |
| PCI-Express | 3 PCI-E 3.0 x16 (8/16/16, 48 lanes), 1 PCI-E 3.0 x4, M.2 Interface: 2 PCI-E 3.0 x4, M.2 Form Factor: 22110/2280, M.2 Key: M-Key (RAID 0,1 support) U.2 Interface: 2 PCI-E 3.0 x4 |
| Integrated On-Board | |
| SATA | SATA3 (6Gbps) via Intel C422 controller RAID 0, 1, 5, 10 support |
| USB | 6 USB 3.0 ports (4 rear + 2 headers), 6 USB 2.0 ports (2 rear + 4 headers), 2 USB 3.1 (2 Type A) |
| LAN | 2 RJ45 Ethernet LAN ports |
| Add-on Options | |
| Raid | Optional |
| Optical Drive | Optional |

| Front Panel | |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|
| LED Indicators | Power LED, Hard drive activity LED, Network activity LED, System Information LED |
| Buttons | Power On/Off button |
| Drive Bays | |
| HDD bays(internal) | 4 Fixed 3.5" drive bays,4x 2.5" fixed drive bays (optional),4 x Hot swap drive bays (optional) |
| Peripheral Bays | 2x 5.25" standard drive bays,2 x 5.25" Standard drive bays (optional) |
| Power Supply | |
| 668W/900W/1200W High Efficiency Power Supply | |
| Cooling System | |
| Cooling System | 1x 12cm rear exhaust fan, Optional 1x 12 cm front cooling fan |
| Optional | Liquid Cooling Technology |
| Form Factor | |
| Form Factor | Mid-Tower |
| Height | : 16.7" (424mm), |
| Width | : 7.6" (193mm), |
| Depth | : 20.68" (525.3mm) |
| <p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p> | |