

Tyrone Camarero Specifications

Tyrone®

Camarero SS400TR-55

Key features

- 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Single Socket P (LGA 3647) supported, CPU TDP support 165W, Up to 28 cores
Note: BIOS version 3.0a or above is required to support 2nd Generation Intel Xeon Scalable Processors-SP
- Intel Intel® C621 chipset
- Up to 1.5TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 1.5TB 3DS ECC LRDIMM, DDR4-2933MHz, in 6 DIMM slots; Up to 1TB Intel Optane DC Persistent Memory in memory mode (Cascade Lake Only)
- 2 PCI-E 3.0 x16, 1 PCI-E 3.0 x8
- 2 GbE LAN ports
- 12 SATA3 (6Gbps) via C621
- Supports 12V DC power input
- I/O: 1 VGA, 2 COM, TPM header
5 USB 3.0 (2 rear, 1 Type-A, 2 via header), 6 USB 2.0 (2 rear, 4 via headers)
- M.2 NGFF connector, M.2 Interface: PCI-E 3.0 x4, Form Factor: 2242, 2280, Key: M-Key, Double Height Connector
- External: 5.25" x 4, 3.5" x 1; Internal: 3.5" x 5 or 2.5" x 5
- Front: 120 x 25 mm x1 PWM Fan, Rear: 120 x 25 mm x1 PWM Fan
- 500/1200W Single PS, 80Plus Platinum



Processor/Cache

Processor	2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Single Socket P (LGA 3647) supported, CPU TDP support 165W, Up to 28 cores Note: BIOS version 3.0a or above is required to support 2nd Generation Intel Xeon Scalable Processors-SP
-----------	--

Chipset

Chipset	Intel® C621 Chipset
---------	---------------------

System Memory

Memory Capacity	Up to 1.5TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 1.5TB 3DS ECC LRDIMM, DDR4-2933MHz, in 6 DIMM slots; Up to 1TB Intel Optane DC Persistent Memory in memory mode (Cascade Lake Only)"
-----------------	---

Expansion Slots

PCI-Express	2 PCI-E 3.0 x16, 1 PCI-E 3.0 x8, M.2 Interface: PCI-E 3.0 x4, Form Factor: 2242, 2280, Key: M-Key, Double Height Connector
-------------	--

Integrated On-Board

SATA	Intel® C621 controller for 12 SATA3 (6 Gbps) ports; RAID 0,1,5,10
LAN	2 1GbE LAN ports
USB	6 USB 2.0 ports (2 rear + 4 headers), 5 USB 3.0 ports (2 rear + 2 headers + 1 Type A)

Add-on Options

Raid Card	Optional
Optical Drive	None

Front Panel

LED	2 Network Activity LEDs, HDD Fail LED, Power Status LED, Power Fail LED, System Information LED
Buttons	Power On/Off button, System Reset Button

Drive Bays

HDD Drives	External: 5.25" x 4, 3.5" x 1; Internal: 3.5" x 5 or 2.5" x 5
------------	--

Power Supply

500/1200W Single PS, 80Plus Platinum

Cooling System

Front: 120 x 25 mm x1 PWM Fan,
Rear: 120 x 25 mm x1 PWM Fan

Form Factor

Tower/Convertible/5U Rackmount

Dimensions: 560 x 200 x 430 mm (22" x 7.9" x 16.9")

Email : info@tyronesystems.com

For more/current product information, visit
www.tyronesystems.com