

Tyrone Camarero Specifications

Camarero SS400TW-14R

Key features

Mainstream, WIO

- Single socket H4 (LGA 1151) supports Intel® Xeon® processor E3-1200 v6/v5, Intel® 7th/6th Gen. Core™ i3 series, Intel® Celeron® and Intel® Pentium®
- Intel® C236 chipset
- 4x 3.5" hot-swap drive bays
- Up to 64GB Unbuffered ECC UDIMM DDR4 2400MHz; 4 DIMM slots
- 2x PCI-E 3.0 x8, 1x PCI-E 3.0 x4 (x8) AOC slot
- 2x GbE ports with Intel® i210-AT 1x dedicated IPMI port
- I/O ports: 1x VGA, 1x COM, 2x USB 2.0, USB 3.0
- 500W Redundant Platinum Level power supplies



Processor/Cache

Processor	Single socket H4 (LGA 1151) supports Intel® Xeon® processor E3-1200 v6/v5, Intel® 7th/6th Gen. Core™ i3 series, Intel® Celeron® and Intel® Pentium®
-----------	---

Chipset

Chipset	Intel® C236 chipset
---------	---------------------

System Memory

Memory Capacity	Up to 64GB Unbuffered ECC UDIMM DDR4 2400MHz; 4 DIMM slots
-----------------	--

Expansion Slots

PCI Express	2x PCI-E 3.0 x8 AOC slots 1x PCI-E 3.0 x4 (in x8) AOC slot 1x M.2 connector
-------------	---

Integrated On-Board

SATA	SATA3 (6Gbps) via C236 controller RAID 0, 1, 5, 10 support
LAN	2x RJ45 Gigabit Ethernet LAN ports , 1x RJ45 dedicated IPMI LAN port

Add-on Options

Raid	Optional
Optical Drive	None

Front Panel

LED	Power LED, Hard drive activity LED, 2x Network activity LEDs, System Overheat LED, Information LED
Buttons	Power On/Off button, System Reset button

Drive Bays

Hot Swap	4x 3.5" Hot-swap SATA3 drive bays
----------	-----------------------------------

Power Supply

500W Redundant Platinum Level power supplies
--

Cooling System

4x 4cm chassis internal fans

Form Factor

Form Factor	1U Rackmount
Width	17.2" (437mm)
Height	1.7" (43mm)
Depth	25.6" (650mm)

Email : info@tyronesystems.com

For more/current product information, visit
www.tyronesystems.com