

Tyrone Camarero Specifications



Camarero SS4COA-28R

Key features

- Intel® 8th/9th Generation Core® i9/Core® i7/Core® i5/Core® i3/Pentium®/Celeron® series Processor, Intel® Xeon® E-2100 Processor, Intel® Xeon® E-2200 Processor. Single Socket LGA-1151 (Socket H4) supported, CPU TDP support Up to 95W TDP"
- Intel® C246
- Up to 128GB Unbuffered ECC/non-ECC UDIMM, DDR4-2666MHz, in 4 DIMM slots
- 1 PCI-E 3.0 x4, 1 PCI-E 3.0 x1, 2 PCI-Ex16 slots are running at NA/16, or 8/8, 1 - 5V PCI 32bit
M.2 Interface: 2 PCI-E 3.0 x4
M.2 Form Factor: 2242/2260/2280/22110
M.2 Key: M-Key
M.2#1~2 are shared with PCI-Ex4 slot, M.2#2 is shared with U.2
U.2 Interface: 1 PCI-E 3.0 x4
- 1 HDMI port, 1 DVI - D port, 1 DP (DisplayPort) port, 1 VGA port, Intel UHD P630 graphic(For CPU Xeon E-21XXG series only)
- Intel® C246 controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Single LAN with Intel® Ethernet Controller I210-AT Shared with IPMI, Single LAN with Intel® PHY I219LM LAN controller
- 8 x 3.5" hot-swap SAS/SATA drive bay w/ full SES-II support on SAS motherboards, 2 x 3.5" fixed drive bay
- 3 x 8cm (7000 RPM) hot-swap PWM cooling fan(s)
- 740/800W Redundant Power supply



Processor/Cache	
Processor	Intel® 8th/9th Generation Core® i9/Core® i7/ Core® i5/Core® i3/Pentium®/Celeron® series Processor, Intel® Xeon® E-2100 Processor, Intel® Xeon® E-2200 Processor. Single Socket LGA-1151 (Socket H4) supported, CPU TDP support Up to 95W TDP
Chipset	
Chipset	Intel® C246
System Memory	
Memory Capacity	Up to 128GB Unbuffered ECC/non-ECC UDIMM, DDR4-2666MHz, in 4 DIMM slots
Expansion Slots	
PCI-Express	1 PCI-E 3.0 x4, 1 PCI-E 3.0 x1, 2 PCI-Ex16 slots are running at NA/16, or 8/8, 1 - 5V PCI 32bit M.2 Interface: 2 PCI-E 3.0 x4 M.2 Form Factor: 2242/2260/2280/22110 M.2 Key: M-Key M.2#1~2 are shared with PCI-Ex4 slot, M.2#2 is shared with U.2 U.2 Interface: 1 PCI-E 3.0 x4
Integrated On-Board	
SATA	Intel® C246 controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10
LAN	2 1GbE LAN ports
Add-on Options	
Raid Card	Optional
Optical Drive	Optional

Front Panel	
LED s	2 Network Activity LEDs, HDD activity LED, Power Status LED, System Information LED
Buttons	Power On/Off button, System Reset Button
Drive Bays	
HDD Bays	8 x 3.5" hot-swap SAS/SATA drive bay w/ full SES-II support on SAS motherboards, 2 x 3.5" fixed drive bay
Peripheral Drives	Optional 1 x slim DVD-ROM drive bay, Optional 2 x USB 2.0 ports, Optional 1 x COM port tray, Optional 2 x USB 3.0 ports
Power Supply	
	740/800W Redundant Power supply
Cooling System	
	3 x 8cm (7000 RPM) hot-swap PWM cooling fan(s)
Form Factor	
Form Factor	2U Rackmount
Height :	3.5" (89 mm),
Width :	17.2" (437 mm),
Depth :	25.5" (647 mm)
<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	

Intel, the Intel logo, the intel inside logo, Xeon and Intel Xeon Phi are trademarks of Intel Corporation in the U.S and /or Other Countries.
Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners