

Tyrone Camarero Specifications

Tyrone®

Camarero SS4C0TI-14

Key features

- **Embedded, Security and Surveillance, Appliance Server, Secure Storage, Rack Workstation**
- Single socket H4 (LGA 1151) supports Intel® Xeon® processor E3-1200 v6/v5, Intel® 7th/6th Gen. Core™ i7/i5/i3 series, Intel® Celeron® and Intel® Pentium®
- Intel® C236 chipset
- 4 Hot-swap 3.5" SATA3 bays, Intel RST
- Up to 64GB Unbuffered Non-ECC UDIMM DDR4 2400MHz; 4 DIMM slots
- 1 PCI-E 3.0 x16 slot
- 1 GbE LAN w/ Intel® i210-AT, 1 GbE LAN w/ Intel® PHY i219LM
- Integrated IPMI 2.0 and KVM with Dedicated LAN
- 1 VGA, 2 COM, 4 USB 3.0, 2 USB 2.0, 1 SuperDOM (shared) audio header
- 4 Hot-swap 3.5" SATA3 drive bays
- 350W Platinum Level Power Supply



Processor/Cache	
Processor	Single socket H4 (LGA 1151) supports Intel® Xeon® processor E3-1200 v6/v5, Intel® 7th/6th Gen. Core™ i7/i5/i3 series, Intel® Celeron® and Intel® Pentium®
Chipset	
Chipset	Intel® C236 chipset
System Memory	
Memory Capacity	4x 288-pin DDR4 DIMM slots, Up to 64GB DDR4 Non-ECC UDIMM
Expansion Slots	
PCI-Express	1 PCI-E 3.0 x16 slot
Integrated On-Board	
SATA	4x SATA3 (6Gbps) via Intel® C236 controller RAID 0, 1, 5, 10 support
LAN	2 RJ45 Gigabit Ethernet LAN ports, 1 RJ45 Dedicated IPMI LAN port
Add-on Options	
Raid	Optional
Optical Drive	None

Front Panel	
LED Indicators	Power LED, Hard drive activity LED, 2 Network activity LEDs, System Overheat LED
Buttons	Power On/Off button, System Reset button
Drive Bays	
HDD bays	4 Hot-swap 3.5" SATA3 drive bays
Power Supply	
	350W Platinum Level Power Supply
Cooling System	
	4x 4cm internal fans
Form Factor	
Form Factor	1U Rackmount
Height	: 1.7" (43mm),
Width	: 17.2" (437mm),
Depth	: 19.85" (503mm)
<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit www.tyronesystems.com</p>	