

# Tyrone Camarero Specifications

Camarero SS4C0TR-34R

## Key features

- Single socket H4 (LGA 1151) supports Intel® Xeon® processor E3-1200 v5, Intel® 6th Gen. Core™i3 series, Intel® Celeron® and Intel® Pentium®
- Intel® C232 chipset
- Up to 64GB Unbuffered ECC UDIMM DDR4 2133MHz; 4x DIMM slots
- 1 PCI-E 3.0 x8 (in x16), 1 PCI-E 3.0 x8, 1 PCI-E 3.0 x4 (in x8)
- Dual GbE LAN with Intel® i210-AT
- 6x SATA3 (6Gbps) via C232; RAID 0, 1, 5, 10
- I/O: 1x VGA, 1x COM, TPM header
- 2x SuperDOM with built-in power
- 5x USB 3.0 (2 rear + 2 via header + 1 Type A), 6x USB 2.0 (2 rear + 4 via headers)
- Integrated IPMI 2.0 and KVM with Dedicated LAN
- 4x 3.5" internal SAS/SATA HDD Bays. 4X 2.5" internal SAS/SATA HDD (opt.)
- Peripheral Drive Bays: 2x 5.25"
- Cost Effective Desktop, Embedded, Workstation Chassis
- 500W Redundant Power Supplies (PS2)

**Tyrone**<sup>®</sup>



Processor/Cache		Front Panel	
Processor	Single socket H4 (LGA 1151) supports Intel® Xeon® processor E3-1200 v5, Intel® 6th Gen. Core™i3 series, Intel® Celeron® and Intel® Pentium®	LED	Power LED, Hard drive activity LED, Network activity LED, System Information LED
Chipset	Intel® C232 chipset	Buttons	Power On/Off button,
System Memory		Drive Bays	
Memory Capacity	4x 288-pin DDR4 DIMM slots, Up to 64GB DDR4 ECC UDIMM	HDD bays	4x 3.5" SAS/SATA HDD Bays. 4x 2.5" HDD Bays (optional). SAS or enterprise SATA HDD only recommended
Expansion Slots		Perhipheral Bays	2x 5.25" peripheral drive bays
PCI Express	1 PCI-E 3.0 x8 (in x16) slot, 1 PCI-E 3.0 x8 slot, 1 PCI-E 3.0 x4 (in x8) slot	Power Supply	
Integrated On-Board		500W Redundant Power Supplies (PS2)	
SATA	SATA3 (6Gbps) via C232 controller RAID 0, 1, 5, 10 support	Cooling System	
LAN	2x RJ45 Gigabit Ethernet LAN ports, 1x RJ45 Dedicated IPMI LAN port	1x 12cm (1850rpm) rear exhaust fan, 1x 12cm (1850rpm) front cooling fan (opt.), Optimized Cooling Technology at 21dB Whisper-Quiet Operation	
Add-on Options		Form Factor	
Raid Card	Optional	Form Factor	Mid Tower
Optical Drive	Optional	Width:	7.6" (193 mm),
		Height:	16.7" (424 mm),
		Depth:	20.68" (525.3 mm)

**Email : [info@tyronesystems.com](mailto:info@tyronesystems.com)**

**For more/current product information, visit**

**[www.tyronesystems.com](http://www.tyronesystems.com)**