

Tyrone Camarero Specifications

Camarero SS4i0TR-55L-300F

Key features

- Intel® Core i7 X-series Processor, Intel® Core i9 Extreme X-series Processor, Intel® Core i9 X-series Processor. , Socket R4 (LGA 2066) supported, CPU TDP support 165W TDP
- Intel® X299
- 128GB Unbuffered non-ECC UDIMM, DDR4-2666MHz, in 8 DIMM slots
- 4 PCI-E 3.0 x16, 4xPCI-E3.0 x16 Slots(8/NA/16/16 or 8/8/8/16(Core i9) or NA/4/8/16(Core i7), M.2 Interface: 2 PCI-E 3.0 x4, RAID 0 & 1, Form Factor: 2280, Key: M-Key, M-Key for SSD and Optane
- 1 VGA port
- 6 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Single LAN with Intel® Ethernet Controller I210-AT, Single LAN with Aquantia® AQC107 10G Ethernet Controller
- Drive bays: External: 5.25" x 4, 3.5" x 1, Internal: 3.5" or 2.5" x 5
- Front: 120 x 25 mm x1 PWM Fan, Rear: 120 x 25 mm x1 PWM Fan
- 500/1200W Single PS , 80 Plus platinum



Processor/Cache

Processor	Intel® Core i7 X-series Processor, Intel® Core i9 Extreme X-series Processor, Intel® Core i9 X-series Processor. , Socket R4 (LGA 2066) supported, CPU TDP support 165W TDP
-----------	---

Chipset

Chipset	Intel® X299
---------	-------------

System Memory

Memory Capacity	128GB Unbuffered non-ECC UDIMM, DDR4-2666MHz, in 8 DIMM slots
-----------------	---

Expansion Slots

PCI-Express	4 PCI-E 3.0 x16, 4xPCI-E3.0 x16 Slots (8/NA/16/16 or 8/8/8/16(Core i9) or NA/4/8/16(Core i7), M.2 Interface: 2 PCI-E 3.0 x4, RAID 0 & 1, Form Factor: 2280, Key: M-Key, M-Key for SSD and Optane
-------------	--

Integrated On-Board

SATA	6 SATA3 (6 Gbps) ports; RAID 0,1,5,10
------	---------------------------------------

LAN	1 RJ45 GbE port (IPMI Shared LAN), 1 RJ45 10GBase-T ports
-----	--

Add-on Options

Raid Card	Optional
-----------	----------

Optical Drive	None
---------------	------

Front Panel

LED	Front Control Panel Power Switch, System Rese
-----	---

Buttons	Power On/Off button
---------	---------------------

Drive Bays

HDD Drives	External: 5.25" x 4, 3.5" x 1, Internal: 3.5" or 2.5" x 5
------------	--

Power Supply

500/1200W Single PS , 80 Plus platinum
--

Cooling System

Front: 120 x 25 mm x1 PWM Fan, Rear: 120 x 25 mm x1 PWM Fan
--

Form Factor

Tower/Convertible/ 5U Rackmount

Dimensions: 560 x 200 x 430 mm (22" x 7.9" x 16.9")

Email : info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com