

# Tyrone Camarero Specifications

**Tyrone**

## Camarero SS5W0TA-45L

### Key features

- 10th Generation Intel® Core™ i9/Core™ i7/Core™i5/Core™i3/Pentium®/Celeron® Processor, Intel® Xeon® W-1200 Processors , Single Socket LGA-1200 (Socket H5) supported, CPU TDP support Up to 125W TDP, Up to 10 cores
- Intel® W480
- 128GB Unbuffered ECC/non-ECC UDIMM, DDR4-2933MHz, in 4 DIMM slots
- 1 PCI-E 3.0 x4,2 PCI-E 3.0 x16 slots (16/NA or 8/8),1 PCI-E 3.0 x1, 1 - 5V PCI 32bit, M.2 Interface: 2 PCI-E 3.0 x4, RAID 0 & 1 M.2 Form Factor: 2280/22110, M.2 Key: M-Key
- 1 DP (DisplayPort) port, 1 HDMI port, 1 DVI - D port
- Intel® W480 controller for 4 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Single LAN with Intel® PHY I219LM LAN controller for AMT/vPro, Single LAN with Intel® Ethernet i225V
- External: 5.25" x 4, 3.5" x 1; Internal: 3.5" x 5 or 2.5" x5
- Front: 120 x 25 mm x1 PWM Fan,Rear: 120 x 25 mm x1 PWM Fan
- 500/1200W Single / Redundant Power Supply, 80Plus Platinum



### Processor/Cache

**Processor** 10th Generation Intel® Core™ i9/Core™ i7/Core™i5/ Core™i3/Pentium®/Celeron® Processor, Intel® Xeon® W-1200 Processors , Single Socket LGA-1200 (Socket H5) supported, CPU TDP support Up to 125W TDP, Up to 10 cores

### Chipset

**Chipset** Intel® W480

### System Memory

**Memory Capacity** 128GB Unbuffered ECC/non-ECC UDIMM, DDR4-2933MHz, in 4 DIMM slots

### Expansion Slots

**PCI-Express** 1 PCI-E 3.0 x4,2 PCI-E 3.0 x16 slots (16/NA or 8/8),1 PCI-E 3.0 x1, 1 - 5V PCI 32bit, M.2 Interface: 2 PCI-E 3.0 x4, RAID 0 & 1 M.2 Form Factor: 2280/22110, M.2 Key: M-Key

### Integrated On-Board

**SATA** Intel® W480 controller for 4 SATA3 (6 Gbps) ports; RAID 0,1,5,10

**LAN** 1 RJ45 Gigabit Ethernet LAN ports, 1 RJ45 2.5 Gigabit Ethernet LAN port

### Add-on Options

**Raid Card** Optional

**Optical Drive** None

### Front Panel

**Front Panel** Front Control Panel Power Switch, System Reset

**Buttons** Power On/Off button

### Drive Bays

**HDD Bays** External: 5.25" x 4, 3.5" x 1; Internal: 3.5" x 5 or 2.5" x5

### Power Supply

500/1200W Single / Redundant Power Supply, 80Plus Platinum

### Cooling System

Front: 120 x 25 mm x1 PWM Fan,  
Rear: 120 x 25 mm x1 PWM Fan

### Form Factor

**Form Factor** Tower/Convertible/5U Rackmount

**Dimensions:** 560 x 200 x 430 mm (22.0" x 7.9" x 16.9")

**Email : [info@tyronesystems.com](mailto:info@tyronesystems.com)**

**For more/current product information, visit [www.tyronesystems.com](http://www.tyronesystems.com)**