

Tyrone Camarero Specifications

Tyrone[®]

Camarero SSA70Ti-45L

Key features

- Single AMD EPYC™ 7003/7002 Series Processor, (7003 Series Processor drop-in support requires BIOS version 2.0 or newer) Socket SP3, Up to 64 Cores
- System on Chip
- 8 DIMM slots, Supports up to 2TB Registered ECC DDR4 3200MHz SDRAM, 8-channel memory bus
- 5 PCI-E 4.0 x16, 2 PCI-E 4.0 x8, M.2, Interface: 2 PCI-E 4.0 x4, Form factor: 2280, 22110, Key: M-key
- 8 SATA3, 2 M.2, 8 SATA3 or 2 NVMe via single SlimSAS x8
- 2 Gigabit Ethernet LAN Ports
- ASPEED AST2500 BMC graphics
- Up to 6 USB 3.0 ports (4 rear + 2 via header)
- 7 PWM 4-pin Fans with tachometer status monitoring
- External: 5.25" x 4, 3.5" x 1; Internal: 3.5" x 5 or 2.5" x 5
- Front:120 x 25 mm x1 PWM Fan, Rear: 120 x 25 mm x1 PWM Fan
- 500 / 1200W Single Power supply ,80 Plus platinum



Processor/Cache

| | |
|-----------|--|
| Processor | Single AMD EPYC™ 7003/7002 Series Processor, (7003 Series Processor drop-in support requires BIOS version 2.0 or newer) Socket SP3, Up to 64 Cores |
|-----------|--|

Chipset

| | |
|---------|----------------|
| Chipset | System on Chip |
|---------|----------------|

System Memory

| | |
|-----------------|--|
| Memory Capacity | 8 DIMM slots, Supports up to 2TB Registered ECC DDR4 3200MHz SDRAM, 8-channel memory bus |
|-----------------|--|

Expansion Slots

| | |
|-------------|---|
| PCI-Express | 5 PCI-E 4.0 x16, 2 PCI-E 4.0 x8, M.2, Interface: 2 PCI-E 4.0 x4, Form factor: 2280, 22110, Key: M-key |
|-------------|---|

Integrated Onboard

| | |
|------|---|
| SATA | 8 SATA3 (6 Gbps) ports |
| LAN | 2 RJ45 Gigabit Ethernet LAN ports, 1 RJ45 Dedicated IPMI LAN port |

Add-on Options

| | |
|----------------|----------|
| Raid Card: | Optional |
| Optical Drive: | None |

Front Panel

| | |
|-------------|---|
| Front Panel | Front Control Panel Power Switch, System Reset, USB 3.0 x 2 |
|-------------|---|

| | |
|---------|---------------------|
| Buttons | Power On/Off button |
|---------|---------------------|

Drive Bays

| | |
|----------|---|
| HDD Bays | External: 5.25" x 4, 3.5" x 1; Internal: 3.5" x 5 or 2.5" x 5 |
|----------|---|

Power Supply

500 / 1200W Single Power supply ,80 Plus platinum

Cooling System

Front:120 x 25 mm x1 PWM Fan,
Rear: 120 x 25 mm x1 PWM Fan

Form Factor

| | |
|-------------|---|
| Form Factor | 5U Rackmount/tower/Convertible |
| Dimensions: | 560 x 200 x 430 mm (22" x 7.9" x 16.9") |

Email : info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com