Tyrone Camarero Specifications

Tyrone

Camarero SSA720TR-212RL

Key features

- Single AMD EPYC™ 7003/7002 Series Processor(7003 Series Processor drop-in support requires BIOS version 2.0 or newer) Socket SP3, Up to 64 Cores
- System on Chip
- 2TB Registered ECC DDR4 3200MHz SDRAM in 8 DIMMs
- 5 PCI-E 4.0 x16, 2 PCI-E 4.0 x8, M.2 Interface: 2 PCI-E 4.0 x4, Form factor: 2280, 22110, Key: M-key
- 8 SATA3, 2 M.2,8 SATA3 or 2 NVMe via single SlimSAS x8
- 2 Gigabit Ethernet LAN Ports
- ASPEED AST 2500 BMC graphics
- Up to 6 USB 3.0 portS (4 rear + 2 via header)
- 7 PWM 4-pin Fans with tachometer status monitoring
- \sim 12 x 3.5"" hot-swap SAS/SATA drive bay with SES3, Optional 2 x 2.5"" hot-swap drive bay
- 3 x 8cm high-performance PWM fan(s)
- 600W/650W/920W/1200W/1000W/ Redundant Power Supply





Processor/Cache

Processor Single AMD EPYC™ 7003/7002 Series Processor

(7003 Series Processor drop-in support requires

BIOS version 2.0 or newer) Socket SP3,

Up to 64 Cores

Chipset

Chipset System on Chip

System Memory

Memory Capacity 2TB Registered ECC DDR4 3200MHz

SDRAM in 8 DIMMs

Expansion Slots

PCI-Express 5 PCI-E 4.0 x16, 2 PCI-E 4.0 x8, M.2

Interface: 2 PCI-E 4.0 x4,

Form factor: 2280, 22110, Key: M-key

Integrated Onboard

SATA 8 SATA3 (6 Gbps)

LAN 2 RJ45 10GBase-T ports;1 RJ45 Dedicated

IPMI LAN port

Add-on Options

Raid Card: Optional
Optical Drive: None

Front Panel

LEDs: 2 Network Activity LEDs;Fan Fail/System

Over Heat LED;HDD activity LED;Power Status LED;Unit Identification (UID) LED

Buttons: Power On/Off button; System Reset Button

Drive Bays

HDD Bays 12 x 3.5"" hot-swap SAS/SATA drive

bay with SES3, Optional 2 x 2.5"" hot-swap

drive bay

Power Supply

600W/650W/920W/1200W/1000W/ Redundant Power Supply

Cooling System

3 x 8cm high-performance PWM fan(s)

Form Factor

Form Factor 2U Rackmount

Dimensions: Height: 3.5" (89 mm);

Width: 17.2" (437 mm); Depth: 25.5" (647 mm)

Email: info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com

AMD the AMD logo inside are trademarks of Advanced Micro Devices in US and / Orother Countries