

Tyrone Camarero Specifications

Tyrone

Camarero SSI100C3A-55



Key features

Workstation

- 3rd Gen Intel® Xeon® Scalable processors, Intel® Xeon® W-3300 Processor, Single Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP
- Intel® C621A
- Single LAN with Intel® Ethernet Controller I210-AT, Single LAN with Marvell AQC113, Single LAN with Realtek RTL8211F PHY (dedicated IPMI)
- Up to 4TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-3200MHz, Up to 4TB Intel® Optane™ Persistent Memory, DDR4-3200MHz, in 16 DIMM slots
- 4 PCI-E 4.0 x16, 3 PCI-E 4.0 x8 (in x16 slot), M.2 Interface: 4 PCI-E 4.0 x4, M.2 Form Factor: 2260/2280/22110, M.2 Key: M-Key
M.2 support to RAID 0,1, 5, 10, VROC key is required for RAID.
- Intel® C621A controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA port, VGA connector is dedicated for IPMI.
- HDD bays: External: 5.25" x 4, 3.5" x 1; Internal: 3.5" x 5 or 2.5" x5
- Front: 120 x 25 mm x1 PWM Fan, Rear: 120 x 25 mm x1 PWM Fan
- 550/1200W Redundant Power Supply
Optional : 500/1200W Single Power Supply

Processor/Cache

Processor 3rd Gen Intel® Xeon® Scalable processors, Intel® Xeon® W-3300 Processor, Single Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP

Chipset

Chipset Intel® C621A

System Memory

Memory Capacity Up to 4TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-3200MHz, Up to 4TB Intel® Optane™ Persistent Memory, DDR4-3200MHz, in 16 DIMM slots

Expansion Slots

PCI-Express 4 PCI-E 4.0 x16, 3 PCI-E 4.0 x8 (in x16 slot), M.2 Interface: 4 PCI-E 4.0 x4, M.2 Form Factor: 2260/2280/22110, M.2 Key: M-Key M.2 support to RAID 0,1, 5, 10, VROC key is required for RAID."

Integrated Onboard

SATA Intel® C621A controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10
LAN 1 RJ45 Dedicated IPMI LAN port, 1 RJ45 Gigabit Ethernet LAN ports, 1 RJ45 10GBase-T ports

Add-on Options

Raid Card Optional
Optical Drive None

Front Panel

LEDs Front Control Panel Power Switch, System Reset
Buttons Power On/Off button

Drive Bays

HDD Bays External: 5.25" x 4, 3.5" x 1; Internal: 3.5" x 5 or 2.5" x5
Peripheral Bay Optional 1 x Slim DVD-ROM Drive, Optional 1 x USB + COM port tray

Power Supply

550/1200W Redundant Power Supply
1200W Single Power Supply

Cooling System

Front: 120 x 25 mm x1 PWM Fan,
Rear: 120 x 25 mm x1 PWM Fan

Form Factor

Form Factor Tower/5U Rackmount
Dimensions 560 x 200 x 430 mm (22" x 7.9" x 16.9")

Email : info@tyronesystems.com

For more/current product information, visit www.tyronesystems.com