

Tyrone Camarero Specifications

Camarero SSi00TR-45

Key features

- Intel® 8th/9th Generation Core™ i9/Core™ i7/Core™i5/Core™i3/Pentium®/Celeron® series Processor., Single Socket H4 (LGA 1151) supported, CPU TDP support Up to 120W TDP
- Intel® Z390 Express
- Up to 64GB Unbuffered non-ECC UDIMM, in 4 DIMM slots (Limited to Gen 8th series and Gen 9th core i3, Pentium and Celeron)
Up to 128GB Unbuffered non-ECC UDIMM, in 4 DIMM slots (Limited to Gen 9th core i5/i7/i9)
- 2 PCI-E 3.0 x16 slots (16/NA or 8/8), 1 PCI-E 3.0 x4, 3 PCI-E 3.0 x1, CPU Slot3 PCI-E 3.0 x8 (IN x16) slot and CPU Slot1 PCI-E 3.0 x4 slot share the same PCI-Ex16 link with CPU Slot6 PCI-E 3.0 x16 slot. CPU Slot6 PCI-E 3.0 x16 slot and CPU Slot3 PCI-E 3.0 x8 (IN x16) slot will change to PCI-E 3.0 x8 link and PCI-E 3.0 x4 link respectively when an add-on card is installed in CPU Slot1 PCI-E 3.0 x4 slot, M.2 Interface: 2 PCI-E 3.0 x4, RAID 0 & 1, M.2 Form Factor: 2242/2260/2280/22110, M.2 Key: M-Key, M-Key
- 2 DP (DisplayPort) ports, 1 HDMI port, DP up to 1.2; HDMI up to 1.4b
- Intel® Z390 Express controller for 6 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Single LAN with Intel® single Ethernet PHY i219V
- External: 5.25" x 4, 3.5" x 1; Internal: 3.5" x 5 or 2.5" x5
- 120 x 25 mm x1 PWM Fan, Rear: 120 x 25 mm x1 PWM Fan
- 500/1200W Single PS, , 80Plus Platinum

Tyrone®



Processor/Cache

Processor	Intel® 8th/9th Generation Core™ i9/Core™ i7/Core™i5/Core™i3/Pentium® /Celeron® series Processor., Single Socket H4 (LGA 1151) supported, CPU TDP support Up to 120W TDP
-----------	---

Chipset

Chipset	Intel® Z390 Express
---------	---------------------

System Memory

Memory Capacity	Up to 64GB Unbuffered non-ECC UDIMM, in 4 DIMM slots (Limited to Gen 8th series and Gen 9th core i3, Pentium and Celeron) Up to 128GB Unbuffered non-ECC UDIMM, in 4 DIMM slots (Limited to Gen 9th core i5/i7/i9)
-----------------	--

Expansion Slots

PCI Express	2 PCI-E 3.0 x16 slots (16/NA or 8/8), 1 PCI-E 3.0 x4, 3 PCI-E 3.0 x1, CPU Slot3 PCI-E 3.0 x8 (IN x16) slot and CPU Slot1 PCI-E 3.0 x4 slot share the same PCI-Ex16 link with CPU Slot6 PCI-E 3.0 x16 slot. CPU Slot6 PCI-E 3.0 x16 slot and CPU Slot3 PCI-E 3.0 x8 (IN x16) slot will change to PCI-E 3.0 x8 link and PCI-E 3.0 x4 link respectively when an add-on card is installed in CPU Slot1 PCI-E 3.0 x4 slot, M.2 Interface: 2 PCI-E 3.0 x4, RAID 0 & 1, M.2 Form Factor: 2242/2260/2280/22110, M.2 Key: M-Key, M-Key
-------------	---

Integrated On-Board

SATA	Intel® Z390 Express controller for 6 SATA3 (6 Gbps) ports; RAID 0,1,5,10
LAN	1 RJ45 Gigabit Ethernet LAN ports

Front Panel

Front Panel	Power Switch, System Reset, USB 3.0 x 2
-------------	---

Add -on Options

Raid	Optional
Optical Drive	None

Drive Bays

External:	5.25" x 4, 3.5" x 1;
Internal:	3.5" x 5 or 2.5" x5

Power Supply

500/1200W Single PS, , 80Plus Platinum

Cooling System

120 x 25 mm x1 PWM Fan, Rear: 120 x 25 mm x1 PWM Fan

Form Factor

Form Factor	5U Rackmount
Dimension	12" x 9.6" (30.48cm x 24.38cm)

Email : info@tyronesystems.com

For more/current product information, visit www.tyronesystems.com