

Camarero TDI100C3R-212

Key features

- Intel Dual Socket Ice Lake Solution LGA4189, Max 230W TDP CPU
- Intel 621A chipset
- 16 DIMM slots (8 per CPU), Max 4TB memory. Optane supported
- 1 x 1000Base-T (i210-AT), 2 x 10GBase-T (X550-AT2), 1 x Dedicated Management Port
- 12 x SATA ports
- 1 VGA, 2 USB 3.0, 1 COM with Micro USB connector
- 4 x PCIe x16
- Aspeed AST2500 Graphics
- IPMI 2.0 with dedicated port
- 12 x 3.5" drive bays
- 6 cooling fans
- 2x1300W / 2 x 1600W or 2 x 2000W Redundant Power Supply



Processor/Cache		Add-on Options	
Processor	Intel Dual Socket Ice Lake Solution LGA4189, Max 230W TDP CPU	Raid Card	Optional
Chipset	Intel 621A chipset	Optical Drive	None
System Memory		Drive Bays	
Memory Capacity	16 DIMM slots (8 per CPU), Max 4TB memory. Optane supported	HDD Bays	12 x 3.5" drive bays
Expansion Slots		Power Supply	
PCI-Express	4 x PCIe x16	2x1300W / 2 x 1600W or 2 x 2000W Redundant Power Supply	
Integrated Onboard		Cooling System	
SATA	12 x SATA ports, RAID 0,1,5,10	6 cooling fans	
LAN	1 x 1000Base-T (i210-AT), 2 x 10GBase-T (X550-AT2), 1 x Dedicated Management Port	Form Factor	
IPMI	IPMI 2.0 with dedicated port	Form Factor	2U Rackmount
<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit www.tyronesystems.com</p>			