

# Tyrone Camarero Specifications

**Tyrone**<sup>®</sup>

Camarero DS40012E1-460RL

## Key features

- Corporate Database, Database Processing & Storage, Enterprise Server, HPC, Data Center. iSCSI SAN
- 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 3 UPI up to 10.4 GT/s
- Intel® C621 chipset
- Up to 6TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 6TB 3DS ECC LRDIMM, DDR4-2933MHz, in 24 DIMM slots; Up to 6TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only).;
- 2 PCI-E 3.0 x16, 1 PCI-E 3.0 x8, 1 SIOM card support (flexible networking), Note: must bundle with Network card
- 60 Hot-swap 3.5" SAS3/SATA3 drive bays with SES3; 2 rear Hot-swap 2.5" drive bays; optional 6 NVMe bays
- Broadcom 3008 SAS3, IT mode
- Server remote management: IPMI 2.0 / KVM over LAN / Media over LAN
- 5 Hot-swap 8cm rear exhaust PWM fans
- 2000W Redundant Power Supplies Titanium Level (96%)



Processor/Cache		Front Panel	
Processor	2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 3 UPI up to 10.4 GT/s	Led's	Power status LED, Hard drive activity LED, Network activity LEDs, System Overheat LED, Power fail LED
Chipset	Intel® C621 chipset	Buttons	Power On/Off button, System Reset button
System Memory		Drive Bays	
Memory Capacity	Up to 6TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 6TB 3DS ECC LRDIMM, DDR4-2933MHz, in 24 DIMM slots; Up to 6TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only).	HDD bays	60 Hot-swap 3.5" SAS3/SATA3 drive bays, 2 Rear Hot-swap 2.5" SATA drive bays
Expansion Slots		Power Supply	
PCI-Express	2 PCI-E 3.0 x16, 1 PCI-E 3.0 x8, 1 SIOM card support (flexible networking), Note: must bundle with Network card	2000W Redundant Power Supplies Titanium Level (96%)	
Integrated On-Board		Cooling System	
SAS	SAS3 (12Gbps) via Broadcom 3008 AOC, IT Mode	5 Hot-swap 8cm rear exhaust PWM fans	
SATA	SATA3 (6Gbps); RAID 0, 1, 5, 10	Form Factor	
LAN	1 RJ45 Dedicated IPMI LAN port	Form Factor	4U Rackmount
Add-on Options		Width	17.2" (437mm),
Optical Drive	None	Height	7" (178mm),
		Depth	30.2" (767mm)
		<p><b>Email : <a href="mailto:info@tyronesystems.com">info@tyronesystems.com</a></b></p> <p><b>For more/current product information, visit</b></p> <p><b><a href="http://www.tyronesystems.com">www.tyronesystems.com</a></b></p>	

© Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of Intel Corporation in the U.S and/or other countries  
 © Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners