TyroneVERTA

Verta D2-SJC-444S

2			
		- () • • • • • • • • • •	- (C) •
			E 🖸 📒
			Tyron

Simplicity and flexibility to scale.

The era of having multiple units for different storage needs is passing, as diverse storage products prevent optimum utilization and can be difficult to manage. Verta series from Tyrone Systems, consolidates all your storage requirements.

Features	Detailed Specifications		
Form Factor	4U SAS3 JBOD storage chassis		
Controller	Single Controller		
Bays	44 x 3.5" hot-swappable HDDs bays		
Power Supply Unit	1200W Redundant Titanium level power supplies		
System Cooling (per node)	7x 8cm (middle) hot-swap redundant cooling fans		
Drive Interface	SAS		
Supported Drives	SAS/SATA LFF/SFF HDDs/SSDs		
Environmental Specifications	Operating temp: 5°C ~35°C / Non Operating temp: -40°C~ 70°C / Operating Relative humidity: 8%~90%		
Packaging Size (W x D x H)	27.2" (691 mm) x 17.4" (442 mm) x 39.6" (1006 mm)		
Weight (without HDDs)	48.00 kg		
Mounting	Standard: 28" slide rail		

1: The protocols are interface specific and not all protocols work with all interfaces_e.g. FC target requires FC ports. Not all protocol options are available for all clients e.g. SRP is not available for MAC OS. 2: Not all host interfaces combinations are available. For e.g. it is not possible to have 12 Gigabit ports + 4 10G ports in the same unit. 3: SSD acceleration uses up to 4 HDD bays for populating SSDs reducing the number of available bays.



For enquiries reach us at: Email: info@tyronesystems.com | www.tyronesystems.com **CONNECT WITH US**

facebook.com/tyronesystems

Stwitter.com/tyronesystems

blog/tyronesystems.com

youtube.com/tyronesystems